

**NAME**

**history** - irccd history plugin

**DESCRIPTION**

The **history** plugin is used to check when someone has been seen for the last time on a channel. For that purpose, irccd needs to be on that channel forever if possible.

**INSTALLATION**

The plugin **history** is distributed with irccd. To enable it add the following to your plugins section:

```
[plugins]
history = ""
```

**USAGE**

The plugin **history** only reacts to the special command. It understands *seen* and *said* sub commands.

- The sub command *seen* tells you when the user has been seen for the last time.
- The sub command *said* tells you what the user has said for the last time.

## Example

```
markand: !history seen jean
irccd: markand, the last time I've seen jean was on 18/01/1989 at 20:55
markand: !history said jean
irccd: markand, the last thing that jean said was: hello world
```

**CONFIGURATION**

The following options are available under the *[plugin.history]* section:

<i>file</i> (string)	path to the JSON file for saving information (Optional. default to cache directory).
----------------------	--

**TEMPLATES**

The **history** plugin supports the following templates in *[templates.history]* section:

<i>error</i>	Template when an internal error occurred. Keywords:
<i>seen</i>	Template for showing last seen. Keywords: <i>target</i> , ( <i>date</i> ).
<i>said</i>	Template for showing the last message. Keywords: <i>message</i> , <i>target</i> , ( <i>date</i> ).

*unknown*      Template when the user has never been seen. Keywords: *target*.

*usage*      Template to show the plugin usage.

All templates support the following standard keywords: *channel*, *command*, *nickname*, *origin*, *plugin*, *server*.

## EXAMPLES

Example of configuration file:

```
[templates.history]
```

```
seen = "#{target} has been seen on #{channel} the last time on: %d/%m/%Y %H:%M"
```

## SEE ALSO

irccd(1), irccd-templates(7)