

NAME

logger - irccd logger plugin

DESCRIPTION

The **logger** plugin may be used to log everything you want. It supports the following events:

- ⊕ onJoin.
- ⊕ onKick.
- ⊕ onMe.
- ⊕ onMessage.
- ⊕ onMode.
- ⊕ onNotice.
- ⊕ onPart.
- ⊕ onTopic.

INSTALLATION

The plugin **logger** is distributed with irccd. To enable it add the following to your plugins section:

```
[plugins]
logger = ""
```

USAGE

The **logger** plugin has no direct commands.

CONFIGURATION

The following options are available under the *[plugin.logger]* section:

file (string) The path to the file where to store logs. Keywords: *channel*, *server*, *(date)*.

TEMPLATES

The **logger** plugin supports the following templates in *[templates.logger]* section:

join Format when someone joins a channel.

kick Format when someone has been kicked. Keywords: *reason*, *target*.

me Format for emote actions. Keywords: *message*.

message Format for channel messages. Keywords: *message*.

mode Format for user mode change. Keywords: *mode*, *limit*, *user*, *mask*.

notice Format on private notices. Keywords: *message*.

part Format when someone leaves a channel. Keywords: *reason*.

topic Format when a topic is changed. Keywords: *topic*.

All templates support the following standard keywords: *channel*, *nickname*, *origin*, *server*.

EXAMPLES

Example of configuration file:

```
[plugin.logger]
file = "/var/log/irccd/#{server}/%y/%m/%d/#{channel}.txt"
```

```
[templates.logger]
join = "user #{nickname} joined #{channel}"
```

SEE ALSO

irccd(1), irccd-templates(7)