

## NAME

**plugin** - irccd plugin plugin

## DESCRIPTION

The **plugin** plugin let you inspect loaded plugins.

## INSTALLATION

The plugin **plugin** is distributed with irccd. To enable it add the following to your plugins section:

```
[plugins]
plugin = ""
```

## USAGE

The **plugin** plugin only reacts to the special command. It understands *info* and *list* sub commands.

- The sub command *info* shows information about a plugin.
- The sub command *list* shows loaded plugins (see configuration for limits).

Both commands work in a channel or as private message with irccd.

## CONFIGURATION

The following options are available under the *[plugin.plugin]* section:

*max-list-lines* (int)            max number of lines allowed for the *list* sub command (Optional, default: 3).

*max-list-columns* (int)        max number of columns allowed per lines (Optional, default: 80).

## TEMPLATES

The **plugin** plugin supports the following templates in *[templates.plugin]* section:

*usage*                        Message to show on invalid usage.

*info*                         Plugin information message to show. Keywords: *author*, *license*, *name*, *summary*, *version*.

*not-found*                    Message to show if a plugin does not exist. Keywords: *name*.

*too-long*                    Message to show if the list of plugin is too long.

All templates support the following standard keywords: *channel*, *command*, *nickname*, *origin*, *plugin*, *server*.

**SEE ALSO**

ircd(1), irccd-templates(7)