

**NAME**

**joke** - irccd joke plugin

**DESCRIPTION**

The **joke** plugin is a convenient command to display jokes in a random order without displaying always the same.

It loads jokes per channel/server pair and display a unique joke each time it is invoked.

**INSTALLATION**

The plugin **joke** is distributed with irccd. To enable it add the following to your plugins section:

```
[plugins]
joke = ""
```

**USAGE**

The **joke** plugin requires a database of jokes file, it consists of a plain JSON file of array of array of strings.

Example of jokes.json file:

```
[
  [
    "Tip to generate a good random password:",
    "Ask a Windows user to quit vim."
  ],
  [
    "Have you tried turning it off and on again?"
  ]
]
```

This file contains two jokes, the first one will be printed on two lines while the second only has one.

Then, invoke the plugin:

```
markand: !joke
irccd: Have you tried turning it off and on again?
markand: !joke
irccd: Tip to generate a good random password:
irccd: Ask a Windows user to quit vim.
```

## CONFIGURATION

The following options are available under the *[plugin.joke]* section:

*file* (string) path to the JSON jokes files (Optional: defaults to data directory/jokes.json).  
Keywords: *channel, server*

Warning: if you use keywords in the **\*\*file\*\*** parameter, you won't have a default joke database anymore.

## TEMPLATES

The **joke** plugin supports the following templates in *[templates.joke]* section:

*error* Template when an internal error occurred. Keywords: *channel, nickname, origin, server*.

## SEE ALSO

irccd(1), irccd-templates(7)